


Agilent 5000 Series Portable Oscilloscopes

Data Sheet





The Next Generation of
Portable Oscilloscopes




Agilent Technologies

The new standard for the everyday scope



Traditional bench scopes are great for characterizing things that you know about. The Agilent's MegaZoom III deep memory and fast update rates help you find the bugs that you don't know about.



- 100 MHz, 300 MHz, and 500 MHz bandwidths
- 2 or 4 channels
- MegaZoom III memory and display technology
 - Up to 1 Mpts acquisition memory (page 4)
 - Up to 100,000 waveforms per second real-time update rate (page 5)
 - High-definition XGA (1024 x 768) display with 256 levels of intensity grading
- Up to 12 bits of vertical resolution, even in single-shot acquisitions (page 7)
- Complete connectivity – standard (page 6)
 - USB (2 host, 1 device)
 - LAN
 - GPIB
 - XGA display out
 - Full remote control, including web browser
 - LXI-class C compliant
- Manuals and in-scope help available in 11 languages
- Secure environment option

If you haven't purchased an Agilent oscilloscope lately, why should you consider one now?

Leading-edge technology for all scope users

The 5000 Series oscilloscopes leverage the same third generation MegaZoom III technology blocks used in our higher performance bench and lab oscilloscopes – **responsive deep memory, fast update rates with minimal "dead time", and analog-like display systems** – and deliver them in a compact package, at a price similar to oscilloscopes with older technology blocks.

Industry-leading customer support

As the world's leading Test and Measurement vendor, Agilent maintains the largest network of sales engineers, application engineers, support engineers and technicians. From pre-sales collaboration, to calibration, to training and consulting, to repair and servicing, Agilent stands with you throughout the life of your product. It's no accident that Agilent has such loyal customers.

Don't take our word for it

Compare the 5000 series with your current bench scope. Or compare it to one of our competitors' newest scopes. You'll see why Agilent has been the **fastest-growing oscilloscope supplier** since 2001 (source: Prime Data 2005 Test Instrument Industry Service Market Share Analysis).

| Model | BW (MHz) | Channels | Maximum sample rate | Memory | Update rate |
|----------|----------|----------|----------------------|------------------------------------|---|
| DS05012A | 100 | 2 | 2 GSa/s | | |
| DS05014A | 100 | 4 | 2 GSa/s | | |
| DS05032A | 300 | 2 | 2 GSa/s | Up to 1 Mpts ¹ (page 4) | Up to 100,000 waveforms per second (page 5) |
| DS05034A | 300 | 4 | 2 GSa/s | | |
| DS05052A | 500 | 2 | 4 GSa/s ¹ | | |
| DS05054A | 500 | 4 | 4 GSa/s ¹ | | |

¹ Maximum sample rate and memory are achieved when two channels are interleaved



Why does deep memory matter?

See more time

This is the most easily understood use of deep memory. The more samples that you acquire, the more time that you can see at a particular sample rate.

Long capture times give you better visibility into cause-effect relationships in your design, which greatly simplifies root-cause debugging. It also allows you to capture start-up events (like the start-up sequence below) in a single acquisition.

You don't have to stitch together multiple acquisitions or set precise triggering conditions. Spend less time finding events, and more time analyzing them.

See more details

The relationship between memory depth and acquisition rate isn't as obvious. All scopes have a "banner" maximum sample rate specification, but many can only sustain these rates at a few timebase settings.



In the case of an oscilloscope with a 5 GSa/s acquisition rate and 10-Kpts of memory (Figure 2), those 10,000 points can only fill 2 ms of time. Since scopes have 10 time divisions, the sample rate drops at any time/div setting below 200 ns/div.

As a result, if you look at "slow/fast" events like a modulated signal, you run the risk of aliasing your signal. Or you may simply miss out on important signal details when you zoom in on it.

Deep memory oscilloscopes let you sustain a high sample rate over longer periods of time.

Always fast, always on

MegaZoom III is the third generation of the fast and deep memory architecture that Agilent introduced in 1996. It's not a special mode, unlike other deep-memory oscilloscopes. You have access to your MegaZoom memory at all times. And the display will respond instantly to your commands as you scale the +/div setting or pan and zoom in the Delayed (or "zoom") window.

You can learn more about MegaZoom III deep memory in Application Note 1446 - *Deep Memory Oscilloscopes: The New Tools of Choice*.




Figure 1.




Figure 2.

Why does a fast update rate matter?

This is a question that we hear frequently. If the human eye has trouble discerning above 30-50 frames per second, **is there really a difference between 3,600 and 100,000 waveforms per second?** If you know what you're looking for, the answer is probably "no". However, if you are hunting for unknown signal anomalies or characterizing jitter, the answer is "yes".




Figure 3. Reducing the dead time between acquisitions ...



Figure 4. ... improves your chances of finding random events like glitches

If you know that there is a **glitch in your system**, it's easy to capture it using a pulse-width trigger. However, if you are just browsing through your design, your chances of finding a glitch increase as the update rate at the oscilloscope increases. If a glitch occurs during the "dead time" between samples, you miss it (Figure 3). With MegaZoom III technology, the dead time is much smaller (Figure 5). A scope with a slower update rate will capture the glitch eventually (if it recurs), but most engineers and technicians don't have the time or patience to wait for their tools to catch up.

If you are **characterizing signal jitter**, a fast update rate gives you accurate results sooner. And when the fast update rate is combined with the 5000 Series' XGA high-definition display (1024 x 768, 256 intensity levels), subtle differences in these acquisitions become obvious.

And like all other aspects of MegaZoom III technology, this is a real-time acquisition mode. **It's always fast, always on.**

Learn more about the benefits of a fast update rate by reading Application Note 1551 - *Improve Your Ability to Capture Elusive Events: Why Oscilloscope Waveform Update Rates are Important.*




Figure 5. Update rates of popular oscilloscopes using their default real-time time acquisition mode

Catch problems sooner and cover more of your debug checklist – our 100,000 waveforms per second update rate helps you find intermittent problems up to 100x faster than comparable scopes

Connectivity

Our customers tell us that oscilloscope connectivity is an increasingly important feature of their test instruments. That's why the 5000 Series scopes come with the most comprehensive hardware and software connectivity tools in their class.

Hardware connectivity

Standard ports include:

- 2 x USB host ports (for external storage and printing devices), one on the front and one on the rear
- 1 x USB device port for high-speed PC connectivity
- 10/100 Mbit LAN for Internet/ Intranet connectivity
- GPIB to allow easy migration into existing test systems
- XGA out for external monitors and projectors



Figure 7. OK, so the 5000 series doesn't have RS-232, But it does have just about any other connection you might need - standard




Figure 6. Agilent Remote Front Panel running in a web browser

LXI class C

LAN eXtensions for Instrumentation (LXI) is a standards-based architecture for test systems. By specifying the interaction of system components, LXI enables fast and efficient test system creation and reconfiguration. The 5000 Series oscilloscopes follow specified LAN protocols, and adhere to LXI requirements such as a built-in Web control server, IVI-COM driver, and easy-to-use SCPI commands. The standard Agilent I/O Library Suite makes it easy to configure and integrate instruments in your system.

IntuiLink toolbars

IntuiLink gives you a quick way to move screenshots and data into Microsoft® Word and Excel. These toolbars can be installed from www.agilent.com/find/intuilink.

View Scope logic analyzer and oscilloscope correlation

View Scope enables simple time-correlated measurements between a 5000 Series oscilloscope and an Agilent 1680/90 or 16800/900 logic analyzer. Scope and logic waveforms are integrated into a single logic analyzer waveform display for easy analysis – all with a simple point-to-point LAN connection. You can also cross-trigger the instruments, automatically de-skew the waveforms, and maintain marker tracking between the instruments.




Figure 8. Combine best-in-class instruments with a simple connection

Other nice features

High resolution mode

Offers up to 12 bits of vertical resolution in real-time, single-shot mode. This is accomplished by serially filtering sequential data points and mapping the filtered results to the display when operating at base time settings greater than 10- μ s/div.

Help is at your fingertips

An embedded help system – available in 11 languages – gives you quick answers if you don't understand a feature. Simply press and hold the corresponding front-panel key, and a screen pops up to explain its function (Figure 9).

Waveform math with FFT

Analysis functions include subtract, multiply, integrate, and differentiate, as well as Fast Fourier Transforms (FFT).

Peak detect

250 ps on 500 MHz models, 500 ps on 300 MHz models and 1 ns on 100 MHz models helps you find narrow glitches.

AutoProbe interface

Automatically sets probe attenuation factors and provides power for selected Infiniium active probes, including the award-winning 1130A 1.5 GHz InfiniMax differential active probe and 1156A 1.5 GHz single-ended active probe systems.

5-digit hardware counter

Measures frequency up to the bandwidth of the scope.

Trig Out

Provides an easy way to synchronize your scope to other instruments. Use the Trig Out port to connect your scope to a frequency counter for more accurate frequency measurements or to cross trigger other instruments.

Autoscale

Displays all active signals, and automatically sets the vertical, horizontal and trigger controls.

23 automatic measurements with QuickMeas

Pressing [QuickMeas] brings up the last four measurements selected. Cursors automatically track the most recently selected measurement.

HDTV Trigger

The 5000 Series supports analog HDTV/EDTV triggering for standards like 1080i, 1080p, 720p and 480p as well as standard video triggering on any line within a field, all lines, all fields, odd or even fields for NTSC, SECAM, PAL and PAL-M video signals.

Easy software upgrades

System software is stored in Flash ROM that can be upgraded from the scope's built-in USB port or LAN. You can find the latest system and IntuiLink Data Capture software at www.agilent.com/find/DSO5000sw.




Figure 9. Press and hold a key for instant help





Figure 10. FFT allows you to view the spectral content of this unfiltered sine wave

Probing

To get the most out of your scope, you need the right probes and accessories for your application. That's why Agilent Technologies offers a complete family of innovative passive and active probes for the 5000 Series scopes to get your job done easily. For more

comprehensive information, refer to the Agilent 6000 and 5000 Series Oscilloscope Probes and Accessories Data Sheet (Agilent publication number 5968-8153EN/ENUS) or visit www.agilent.com/find/scope_probes.



Selection guide

| | 10070C | N2863A (shipped with 100 MHz and 300 MHz models) | 10073C (shipped with 500 MHz models) | 10076A high-voltage probe | N2771A high-voltage probe |
|---|--|---|--|--------------------------------------|---|
| Probe bandwidth | 20 MHz | 300 MHz | 500 MHz | 250 MHz | 50 MHz |
| Probe rise time (calculated) | < 17.5 ns | < 1.16 ns | < 700 ps | < 1.4 ns | < 7 ns |
| Attenuation ratio | 1:1 | 10:1 | 10:1 | 100:1 | 1000:1 |
| Input resistance (when terminated into 1 M Ω) | 1 M Ω | 10 M Ω | 2.2 M Ω | 66.7 M Ω | 100 M Ω |
| Input capacitance | Approx. 70 pF | Approx. 12 pF | Approx. 12 pF | Approx. 3 pF | Approx. 1 pF |
| Maximum input (dc+peak ac) | 400 Vpk CAT I (mains isolated) 400 Vpk CAT II (post receptacle mains) | 300 Vrms | 500 Vpk CAT I (mains isolated) 400 Vpk CAT II (post receptacle mains) | 4000 Vpk | 15 kV dc, 10 kVrms, 30 kV dc + peak ac |
| Compensation range | None | 5-30 pF | 6-15 pF | 6-20 pF | 7-25 pF |
| Probe sense | No | Yes | Yes | Yes | No |
| U.S. price | \$166.00 | \$129.00 | \$280.00 | \$306.00 | \$997.00 |

Probing (continued)

Selection guide (continued)

| Current probes | Description |
|-----------------------|----------------------------------|
| 1147A | 50 MHz 115A current probe, ac/dc |
| 1146A | 100 kHz current probe, ac/dc |
| N2780A | 2 MHz/500A current probe, ac/dc |
| N2781A | 10 MHz/150A current probe, ac/dc |
| N2782A | 50 MHz/30A current probe, ac/dc |
| N2783A | 100 MHz/30A current probe, ac/dc |
| N2779A | Power supply for N278xA |

| Active single-ended probes | Description |
|-----------------------------------|--------------------------------|
| 1141A | 200 MHz differential probe |
| 1144A | 800 MHz active probe |
| 1145A | 2-channel 750 MHz active probe |
| 1142A | Power supply for 1144A/1145A |
| 1156A | 1.5 GHz active probe |

| Active differential probes | Description |
|-----------------------------------|---|
| N2772A | 20 MHz differential probe |
| N2773A | Probe power supply for N2772A |
| 1130A | 1.5 GHz InfiniiMax differential probe amplifier (Order one or more InfiniiMax probe heads or connectivity kits per amplifier.) |

Options

Option SEC – Secure Environment Mode

Provides compliance with National Industrial Security Program Operating Manual (NISPOM) Chapter 8 requirements, which allows you to move the instrument out of a secure area with confidence. Option SEC offers the highest level of security by ensuring that internal memory is clear of all setup and trace settings. When this option is installed, it will store setups and traces to internal volatile memory only. To permanently store data, you can save it to an external memory device via the oscilloscope's front-panel USB port.

E2690B Oscilloscope Tools

Oscilloscope Tool package, licensed by Agilent Technologies from Amherst Systems Associates (ASA), is the most powerful suites of analysis, debug, collaboration and automation tools available for Agilent real-time oscilloscopes. These tools make it easy to perform in-depth analysis of captured signals. More information can be found in the *Oscilloscope Tools* data sheet (Agilent publication number 5989-3525EN).





Figure 12. E2690B Oscilloscope Tools allows in-depth analysis of captured signals.

Need even more measurement power? Consider the DSO/MSO6000 Series.

The 6000 series of oscilloscopes and mixed-signal oscilloscopes offers the same MegaZoom III memory and display technology of the 5000 Series, and adds a wealth of additional capabilities:

- MSO (Mixed Signal Oscilloscope) models with 16 fully-integrated digital channels
- 1 GHz bandwidth models
- 2 Mpts memory standard, 8 Mpts optional
- Hardware serial triggering for buses like I²C, SPI, CAN, LIN, and USB
- Optional hardware-accelerated serial decode FlexRay like I²C, SPI, CAN, and LIN
- Battery option
- Support for Altera and Xilinx FPGAs

You can learn more about the 6000 Series at www.agilent.com/find/mso6000



Performance characteristics

Acquisition

| | |
|-----------------------------|---|
| Sample rate | DSO501xA/503xA: 2 GSa/a each channel DSO505xA: 4 GSa/s half channel ¹ , 2 GSa/s each channel |
| Equivalent-time sample rate | 400 GSa/s (when real-time mode is turned off) |
| Memory depth | 1 Mpts half channel ¹ , 500 kpts each channel |
| Vertical resolution | 8 bits, up to 12 in high-resolution or averaging modes |
| Peak detection | DSO501xA: 1 ns peak detect DSO503xA: 500 ps peak detect DSO505xA: 250 ps peak detect |
| Averaging | Selectable from 2, 4, 8, 16, 32, 64 ... to 65536 |
| High resolution mode | Average mode with #avg = 1 12 bits of resolution when $\geq 10 \mu\text{s}/\text{div}$, at 4 GSa/s or $\geq 20 \mu\text{s}/\text{div}$, at 2 GSa/s |
| Filter | Sinx/x interpolation (single shot BW = sample rate/4 or bandwidth of oscilloscope, whichever is less) with vectors on and in real-time mode |

Vertical system

| | |
|--|---|
| Scope channels | DSO50x2A: 2 Ch 1 and 2 simultaneous acquisition DSO50x4A: Ch 1, 2, 3, and 4 simultaneous acquisition |
| Bandwidth (-3dB) ² | DSO501xA: DC to 100 MHz DSO503xA: DC to 300 MHz DSO505xA: DC to 500 MHz |
| AC coupled | DSO501xA: 3.5 Hz to 100 MHz DSO503xA: 3.5 Hz to 300 MHz DSO505xA: 3.5 Hz to 500 MHz |
| Calculated rise time (= $0.35/\text{bandwidth}$) | DSO501xA: 3.5 nsec DSO503xA: 1.17 nsec DSO505xA: 700 psec |
| Single-shot bandwidth | DSO501xA: 100 MHz DSO503xA: 300 MHz DSO505xA: 500 MHz |

¹ Half channel is when only one channel of channel pair 1-2 is turned on, or one channel of channel pair 3-4 is turned on.

² Denotes warranted specifications, all others are typical. Specifications are valid after a 30-minute warm-up period and $\pm 10^\circ \text{C}$ from firmware calibration temperature.

Performance characteristics (continued)

Vertical system (continued)

| | |
|--|---|
| Range ¹ | 2 mV/div to 5 V/div (1 M Ω or 50 Ω) |
| Maximum input | Maximum input voltage for analog inputs: CAT I 300 Vrms, 400 Vpk; transient overvoltage 1.6 kVpk CAT II 100 Vrms, 400 Vpk with N2863A 10:1 probe: CAT I 600 V, CAT II 300 V (DC + peak AC) with 10073C 10:1 probe: CAT I 500 Vpk, CAT II 400 Vpk with 50 Ω input: 5 Vrms |
| Offset range | ± 5 V on ranges < 10 mV/div; ± 20 V on ranges 10 mV/div to 200 mV/div; ± 75 V on ranges >200 mV/div |
| Dynamic range | ± 8 div |
| Input impedance | 1 M Ω \pm 1% 12 pF or 50 Ω \pm 1.0%, selectable |
| Coupling | AC, DC |
| BW limit | 25 MHz selectable |
| Channel-to-channel isolation | DC to max bandwidth > 40 dB |
| Standard probes | DSO501xA: 10:1 N2863A shipped standard for each oscilloscope channel DSO503xA: 10:1 N2863A shipped standard for each oscilloscope channel DSO505xA: 10:1 10073C shipped standard for each oscilloscope channel |
| Probe ID | Auto probe sense and AutoProbe interface Agilent- and Tektronix-compatible passive probe sense |
| ESD tolerance | ± 2 kV |
| Noise peak-to-peak | DSO501xA: 3% full scale or 2.5 mV, whichever is greater DSO503xA: 3% full scale or 3 mV, whichever is greater DSO505xA: 3% full scale or 3.6 mV, whichever is greater |
| DC vertical gain accuracy ² | $\pm 2.0\%$ full scale |
| DC vertical offset accuracy | ≤ 200 mV/div: ± 0.1 div ± 2.0 mV $\pm 0.5\%$ offset value; > 200 mV/div: ± 0.1 div ± 2.0 mV $\pm 1.5\%$ offset value |
| Single cursor accuracy ¹ | \pm {DC vertical gain accuracy + DC vertical offset accuracy + 0.2% full scale (~1/2 LSB)} <i>Example:</i> for 50 mV signal, oscilloscope set to 10 mV/div (80 mV full scale), 5 mV offset, accuracy = \pm {2.0% (80 mV) + 0.1 (10 mV) + 2.0 mV + 0.5% (5 mV) + 0.2%(80 mV)} = ± 4.785 mV |
| Dual cursor accuracy ¹ | \pm {DC vertical gain accuracy + 0.4% full scale (~1 LSB)} <i>Example:</i> for 50 mV signal, oscilloscope set to 10 mV/div (80 mV full scale), 5 mV offset, accuracy = \pm {2.0% (80 mV) + 0.4% (80 mV)} = ± 1.92 mV |

¹ 2 mV/div is a magnification of 4 mV/div setting. For vertical accuracy calculations, use full scale of 32 mV for 2 mV/div sensitivity setting.

² Denotes warranted specifications, all others are typical. Specifications are valid after a 30-minute warm-up period and ± 10 °C from firmware calibration temperature.

Performance characteristics (continued)

Horizontal

| | |
|--------------------------|--|
| Range | DSO501xA: 5 nsec/div to 50 sec/div DSO503xA: 2 nsec/div to 50 sec/div DSO505xA: 1 nsec/div to 50 sec/div |
| Resolution | 2.5 psec |
| Timebase accuracy | 25 ppm (0.0025%) to 40° C, plus 1 ppm per ° C from 40° C, to 55° C |
| Vernier | 1-2-5 increments when off, ~25 minor increments between major settings when on |
| Delay range | Pre-trigger (negative delay): Greater of 1 screen width or 125 μ s Post-trigger (positive delay): 1 s to 500 seconds |
| Channel delta-t accuracy | Same channel: $\pm 0.0025\%$ reading $\pm 0.1\%$ screen width ± 20 ps Channel-to-channel: $\pm 0.0025\%$ reading $\pm 0.1\%$ screen width ± 40 ps <i>Same channel example (DSO505xA):</i> For signal with pulse width of 10 μ s, oscilloscope set to 5 μ s/div (50 μ s screen width), delta-t accuracy = $\pm\{0.0025\% (10 \mu\text{s}) + 0.1\% (50 \mu\text{s}) + 20 \text{ps}\} = 50.27 \text{ ns}$ |
| Modes | Main, delayed, roll, XY |
| XY | Bandwidth: Max bandwidth Phase error @ 1 MHz: < 0.5 degrees Z Blanking: 1.4 V blanks trace (use external trigger on DSO50x2A, channel 4 on DSO50x4A) |
| Reference positions | Left, center, right |

Trigger system

| | |
|----------------|--|
| Sources | DSO50x2A: Ch 1, 2, line, ext DSO50x4A: Ch 1, 2, 3, 4, line, ext |
| Modes | Auto, Normal (triggered), single |
| Holdoff time | ~60 ns to 10 seconds |
| Trigger jitter | 15 ps rms |

Performance characteristics (continued)

Trigger system (continued)

| | |
|-------------|---|
| Selections | Edge, pulse width, pattern, TV, duration |
| Edge | Trigger on a rising, falling, or alternating edge of any source |
| Pulse width | Trigger when a positive- or negative-going pulse is less than, greater than, or within a specified range on any of the source channels. Minimum pulse width setting: 5 ns (DSO501xA) 2 ns (DSO503xA, DSO505xA) Maximum pulse width setting: 10 s |
| Pattern | Trigger at the beginning of a pattern of high, low, and don't care levels and/or a rising or falling edge established across any of the channels, but only after a pattern has been established for a minimum of 2 nsec. The channel's high or low level is defined by that channel's trigger level. |
| TV | Trigger using any oscilloscope channel on most analog progressive and interlaced video standards including HDTV/EDTV, NTSC, PAL, PAL-M or SECAM broadcast standards. Select either positive or negative sync pulse polarity. Modes supported include Field 1, Field 2, all fields, all lines, or any line within a field. TV trigger sensitivity: 0.5 division of sync signal. Trigger holdoff time can be adjusted in half field increments. |
| Duration | Trigger on a multi-channel pattern whose time duration is less than a value, greater than a value, greater than a time value with a timeout, or inside or outside of a set of time values. Minimum duration setting: 2 ns Maximum duration setting: 10 s |

| | |
|-----------|--|
| AutoScale | Finds and displays all active channels, sets edge trigger mode on highest-numbered channel, sets vertical sensitivity on channels, time base to display ~1.8 periods. Requires minimum voltage > 10 mVpp, 0.5% duty cycle and minimum frequency > 50 Hz. |
|-----------|--|

Channel triggering

| | |
|--------------------------|--|
| Range (internal) | ±6 div from center screen |
| Sensitivity ¹ | < 10 mV/div: greater of 1 div or 5mV; ≥ 10 mV/div: 0.6 div |
| Coupling | AC (~10 Hz), DC, noise reject, HF reject and LF reject (~50 kHz) |

¹ Denotes warranted specifications, all others are typical. Specifications are valid after a 30-minute warm-up period and ±10° C from firmware calibration temperature.

Performance characteristics (continued)

| External (EXT) triggering | DS050x2A | DS050x4A |
|---------------------------|--|---------------------------|
| Input impedance | 1 M Ω \pm 3% 12 pF or 50 Ω \pm 1% | 1.015 k Ω \pm 5% |
| Maximum input | CAT I 300 Vrms, 400 Vpk; transient overvoltage 1.6 kVpk CAT II 100 Vrms, 400 Vpk with N2863A 10:1 probe: CAT I 600 V, CAT II 300 V (DC + peak AC) with 10073C 10:1 probe: CAT I 500 Vpk, CAT II 400 Vpk 5 Vrms with 50-ohm input | \pm 15 V |
| Range | DC coupling: trigger level \pm 1V and \pm 8V | \pm 5 V |
| Sensitivity | For \pm 1V range setting: DC to 100 MHz, 100 mV, >100 MHz to bandwidth of the oscilloscope, 200 mV For \pm 8 V range setting: DC to 100 MHz, 250 mV; >100 MHz to bandwidth of the oscilloscope, 500 mV | DC to 100 MHz, 500 mV |
| Coupling | AC (~10 Hz), DC, noise reject, HF reject and LF reject (~50 kHz) | |
| Probe ID | Auto probe sense and AutoProbe interface Agilent- and Tektronix-compatible passive probe sense | |
| Display system | | |
| Display | 6.3-inch (161 mm) diagonal color TFT LCD | |
| Display update rate | Up to 100,000 waveforms/sec in real-time mode | |
| Resolution | XGA: 768 vertical by 1024 horizontal points (screen area); 640 vertical by 1000 horizontal points (waveform area) 256 levels of intensity scale | |
| Controls | Waveform intensity on front panel. Vectors on/off; infinite persistence on/off, 8 x 10 grid with intensity control | |
| Built-in help system | Key-specific help displayed by pressing and holding key or softkey of interest | |
| Real-time clock | Time and date (user adjustable) | |

Performance characteristics (continued)

Measurement features

| | |
|------------------------|--|
| Automatic measurements | Measurements are continuously updated. Cursors track last selected measurement. |
| Voltage | Peak-to-peak, maximum, minimum, average, amplitude, top, base, overshoot, preshoot, RMS, standard deviation |
| Time | Frequency, period, + width, - width and duty cycle on any channel. Rise time, fall time, X at max Y (time at max volts), X at min Y (time at min volts), delay, and phase on oscilloscope channels only. |
| Counter | Built-in 5-digit frequency counter on any channel. Counts up to the oscilloscope's bandwidth. |
| Threshold definition | Variable by percent and absolute value; 10%, 50%, 90% default for time measurements |
| Cursors | Manually or automatically placed readout of Horizontal (X, ΔX , $1/\Delta X$) and Vertical (Y, ΔY). Additionally oscilloscope channels can be displayed as binary or hex values. |
| Waveform math | One function of 1-2, 1x2, FFT, differentiate, integrate. Source of FFT, differentiate, integrate: oscilloscope channels 1 or 2, 1-2, 1+2, 1x2. |

FFT

| | |
|----------------------|---|
| Points | Fixed at 1000 points |
| Source of FFT | Scope channels 1 or 2 (or 3 or 4 on DS050x4A only), 1+2, 1-2, 1*2 |
| Window | Rectangular, flattop, hanning |
| Noise floor | -50 to -90 dB depending on averaging |
| Amplitude | Display in dBV, dBm at 50 Ω |
| Frequency resolution | 0.05/time per div |
| Maximum frequency | 50/time per div |

Storage

| | |
|-------------------------|---|
| Save/recall | 10 setups and traces can be saved and recalled using internal non-volatile memory. Optional secure environment mode ensures setups and traces are stored to internal volatile memory so data is erased when power is removed. Compliant to NISPOM Chapter 8 requirements. |
| Storage type and format | USB 1.1 host ports on front and rear panels Image formats: BMP (8-bit), BMP (24-bit), PNG (24-bit) Data formats: X and Y (time/voltage) values in CSV format, ASCII XY format, BIN format Trace/setup formats: Recalled |

I/O

| | |
|-----------------------|--|
| Standard ports | USB 2.0 high speed device, two USB 1.1 host ports, 10/100-BaseT LAN, IEEE488.2 GPIB, XGA video output |
| Max transfer rate | IEEE488.2 GPIB: 500 kbytes/sec USB (USBTMC-USB488): 3.5 Mbytes/sec 100 Mbps LAN (TCP/IP): 1 Mbytes/sec |
| Printer compatibility | Selected HP Deskjet printers |

Performance characteristics (continued)

General characteristics

| | |
|---------------|---|
| Physical size | 35.4 cm wide x 18.8 cm high x 17.4 cm deep (without handle) 38.5 cm wide x 18.8 cm high x 17.4 cm deep (with handle) |
|---------------|---|

| | |
|--------|---|
| Weight | Net: 4.1 kg (9 lbs) Shipping: approximately 9 kgs (20 lbs) |
|--------|---|

| | |
|-------------------------------|---------------------------|
| Probe comp output frequency ~ | 1.2 kHz, Amplitude ~2.5 V |
|-------------------------------|---------------------------|

| | |
|-------------|--|
| Trigger out | 0 to 5 V into open circuit (~23 ns delay) 0 to 2.5 V into 50 Ω |
|-------------|--|

| | |
|-----------------|---------------------------------------|
| Kensington lock | Connection on rear panel for security |
|-----------------|---------------------------------------|

Power requirements

| | |
|-------------|--|
| Line rating | ~Line 120 W max, 96-144 V/48-440 Hz, 192-288 V/48-66 Hz, automatic selection |
|-------------|--|

| | |
|----------------|--|
| Line frequency | 50/60 Hz, 100-240 VAC; 440 Hz, 100-132 VAC |
|----------------|--|

| | |
|-------------|-----------|
| Power usage | 110 W max |
|-------------|-----------|

Environmental characteristics

| | |
|---------------------|--|
| Ambient temperature | Operating -10° C to $+55^{\circ}$ C; non-operating -51° C to $+71^{\circ}$ C |
|---------------------|--|

| | |
|--------------------|--|
| Humidity operating | 95% RH at 40° C for 24 hour; non-operating 90% RH at 65° C for 24 hour |
|--------------------|--|

| | |
|----------|---|
| Altitude | Operating to 4,570 m (15,000 ft); non-operating to 15,244 m (50,000 ft) |
|----------|---|

| | |
|-----------|---|
| Vibration | Agilent class GP and MIL-PRF-28800F; Class 3 random |
|-----------|---|

| | |
|-------|--|
| Shock | Agilent class GP and MIL-PRF-28800F (operating 30 g, 1/2 sine, 11-ms duration, 3 shocks/axis along major axis. Total of 18 shocks) |
|-------|--|

| | |
|------------------|---|
| Pollution degree | Normally only dry non-conductive pollution occurs. Occasionally a temporary conductivity caused by condensation must be expected. |
|------------------|---|

| | |
|------------|---------------------------|
| Indoor use | Rated for indoor use only |
|------------|---------------------------|

Other

| | |
|------------------------|---|
| Measurement categories | CAT I: Mains isolated CAT II: Line voltage in appliance and to wall outlet |
|------------------------|---|

| | |
|------------------------|---|
| Regulatory information | Safety IEC 61010-1:2001 / EN 61010-1:2001 Canada: CSA C22.2 No. 61010-1:2004 USA: UL 61010-1:2004 |
|------------------------|---|

| | |
|---------------------------|---|
| Supplementary information | The product herewith complies with the requirements of the Low Voltage Directive 73/23/EEC and the EMC Directive 89/336/EEC, and carries the CE-marking accordingly. The product was tested in a typical configuration with HP/Agilent test systems. Product specifications, characteristics, and descriptions in this document are subject to change without notice. |
|---------------------------|---|

Ordering information

Available models

| Product number | Description |
|----------------|--|
| DSO5012A | 100 MHz, 2-channel portable oscilloscope |
| DSO5014A | 100 MHz, 4-channel portable oscilloscope |
| DSO5032A | 300 MHz, 2-channel portable oscilloscope |
| DSO5034A | 300 MHz, 4-channel portable oscilloscope |
| DSO5052A | 500 MHz, 2-channel portable oscilloscope |
| DSO5054A | 500 MHz, 4-channel portable oscilloscope |

Standard features

| Product number | Description |
|-----------------------|---|
| Warranty | 3-year return-to-Agilent warranty |
| Hardcopy user's guide | |
| ABA | Printed user's guide in English |
| ABD | Printed user's guide in German |
| ABF | Printed user's guide in French |
| ABZ | Printed user's guide in Italian |
| ABJ | Printed user's guide in Japanese |
| AC6 | Printed user's guide in Korean |
| AB9 | Printed user's guide in Portuguese |
| AKT | Printed user's guide in Russian |
| AB2 | Printed user's guide in Simplified Chinese |
| ABE | Printed user's guide in Spanish |
| AB0 | Printed user's guide in Traditional Chinese |
| Power cord | |
| 900 | United Kingdom |
| 901 | Australia/ New Zealand |
| 902 | Continental Europe |
| 903 | United States/ Canada |
| 906 | Switzerland |
| 912 | Denmark |
| 917 | South Africa/ India |
| 918 | Japan |
| 919 | Israel |
| 920 | Argentina |
| 921 | Chile |
| 922 | China |
| 927 | Brazil/ Thailand |
| Probes | One probe per channel DSO501x, DSO503x: N2863A DSO505x: 10073C |
| Software | Agilent IO Libraries |
| Other documentation | Service guide (CD-ROM, English), Certificate of Calibration, Declaration of Conformance |
| Miscellaneous | Protective front cover |

Ordering information (continued)

Options

| Product number | Description | U.S. price |
|----------------|--|------------|
| SEC | Secure Environment Mode – Provides compliance with National Industrial Security Program Operating Manual (NISPOM) Chapter 8 requirements (factory installed option only for new purchase, not retrofittable for existing 5000 Series scope). | \$400 ea. |
| A6J | ANSI Z540-compliant calibration | \$300 ea. |

Available software

| Product number | Description |
|--|---|
| Oscilloscope Tools E2690B | Oscilloscope Tools software (US and Canada) |
| N5385B | Oscilloscope Tools software (International) |
| E2693B | 1 year update subscription for oscilloscope tools (US and Canada) |
| N5388B | 1 year update subscription for oscilloscope tools (International) |
| (You will order Option 005 – Scope Guide. High-bandwidth Agilent oscilloscopes support more comprehensive versions of Oscilloscope Tools. Please refer to Agilent Publication 5989-3525EN: <i>E2690B Oscilloscope Tools</i> for more details.) | |

Accessories

| Product number | Description |
|----------------|--|
| N2916B | Rackmount kit for 6000 and 5000 Series oscilloscopes |
| N2917B | Transit case for 6000 and 5000 Series oscilloscopes |
| N2760A | Soft carrying case for 5000 Series oscilloscopes |

Cable

| Product number | Description |
|----------------|----------------------|
| 10833A | GPIB cable, 1 m long |

Probing

Common probes are listed on page 9. For a more comprehensive list, please refer to the Agilent 6000 and 5000 Series Oscilloscope Probes and Accessories Data Sheet (Agilent publication number 5968-8153EN/ENUS), or visit www.agilent.com/find/scope_probes



Agilent Email Updates

www.agilent.com/find/emailupdates

Get the latest information on the products and applications you select.



Agilent Direct

www.agilent.com/find/agilentdirect

Quickly choose and use your test equipment solutions with confidence.



www.agilent.com/find/open

Agilent Open simplifies the process of connecting and programming test systems to help engineers design, validate and manufacture electronic products. Agilent offers open connectivity for a broad range of system-ready instruments, open industry software, PC-standard I/O and global support, which are combined to more easily integrate test system development.



www.lxistandard.org

LXI is the LAN-based successor to GPIB, providing faster, more efficient connectivity. Agilent is a founding member of the LXI consortium.

Related literature

| Publication title | Publication type | Publication number |
|--|-----------------------|--------------------|
| <i>Agilent Technologies 5000 and 6000 Series Oscilloscope Probes and Accessories</i> | Data Sheet | 5968-8153EN/EUS |
| <i>Option SEC Secure Environment Mode Option for Agilent 5000 Series Oscilloscopes</i> | Data Sheet | 5989-6276EN |
| <i>E2690B Oscilloscope Tools</i> | Data Sheet | 5989-3525EN |
| <i>6000 Series Oscilloscopes</i> | Data Sheet | 5989-2000EN |
| <i>Improve Your Ability to Capture Elusive Events</i> | Application Note 1551 | 5989-2002EN |
| <i>Oscilloscope Display Quality Impacts Ability to Uncover Signal Anomalies</i> | Application Note 1552 | 5989-2003EN |
| <i>Deep Memory Oscilloscopes: The New Tools of Choice</i> | Application Note 1446 | 5988-9106EN |
| <i>Evaluating Oscilloscope Vertical Noise Characteristics</i> | Application Note 1558 | 5989-3020EN |

Remove all doubt

Our repair and calibration services will get your equipment back to you, performing like new, when promised. You will get full value out of your Agilent equipment throughout its lifetime. Your equipment will be serviced by Agilent-trained technicians using the latest factory calibration procedures, automated repair diagnostics and genuine parts. You will always have the utmost confidence in your measurements.

Agilent offers a wide range of additional expert test and measurement services for your equipment, including initial start-up assistance onsite education and training, as well as design, system integration, and project management.

For more information on repair and calibration services, go to

www.agilent.com/find/removealldoubt

Windows® is a U.S. registered trademark of Microsoft Corporation.

www.agilent.com

For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office. The complete list is available at:

www.agilent.com/find/contactus

Phone

Americas

| | |
|---------------|----------------|
| Canada | (877) 894-4414 |
| Latin America | 305 269 7500 |
| United States | (800) 829-4444 |

Asia Pacific

| | |
|-----------|----------------|
| Australia | 1 800 629 485 |
| China | 800 810 0189 |
| Hong Kong | 800 938 693 |
| India | 1 800 112 929 |
| Japan | 81 426 56 7832 |
| Korea | 080 769 0800 |
| Malaysia | 1 800 888 848 |
| Singapore | 1 800 375 8100 |
| Taiwan | 0800 047 866 |
| Thailand | 1 800 226 008 |

Europe

| | |
|----------------|-------------------------------------|
| Austria | 0820 87 44 11 |
| Belgium | 32 (0) 2 404 93 40 |
| Denmark | 45 70 13 15 15 |
| Finland | 358 (0) 10 855 2100 |
| France | 0825 010 700 |
| Germany | 01805 24 6333* *0.14€/minute |
| Ireland | 1890 924 204 |
| Italy | 39 02 92 60 8484 |
| Netherlands | 31 (0) 20 547 2111 |
| Spain | 34 (91) 631 3300 |
| Sweden | 0200-88 22 55 |
| Switzerland | (French) 44 (21) 8113811 (Opt 2) |
| Switzerland | (German) 0800 80 53 53 (Opt 1) |
| United Kingdom | 44 (0) 7004 666666 |

Other European countries:
www.agilent.com/find/contactus

Revised: March 23, 2007

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2007
Printed in USA, April 17, 2007
5989-6110EN



Agilent Technologies